



Newcastle and Chatham collections



DESIGN

Product Type:	Floating SPC
Overall Thickness:	4.7 mm (.185")
Wear Layer:	12 mil (0.3 mm)
Finish:	P.U.
Surface Profile:	Deep Emboss & Slate Emboss & Travertine Emboss
Size:	150mm x 1220mm (actual) 5.9"W x 48"L (nominal) 300mm x 610mm (actual) 11.8"W x 24"L (nominal)
Square Feet Per Carton:	23.64 sf/ctn (2.196 m2/ctn)
Pieces Per Carton:	12 pieces/ctn
Pounds per carton:	32.14 lbs/ctn (14.58 kg/ctn)
Installation Method:	Floating

PERFORMANCE

Construction:	Residential & Commercial Grade Enhanced Resilient Tile
Classification:	ASTM F-1700 - Class III, Type A - Smooth, Type B - Embossed
Squareness:	ASTM F2055 -10 Passes - maximum 0.010 in. (0.25mm)
Size and Tolerance:	ASTM F2055 - Passes - at ± 0.016 in./lin. Ft. (0.4 mm/305 mm)
Thickness:	ASTM F386 - Passes - as specified ± 0.005 in. (0.13 mm)
Flexibility:	ASTM F137 - Passes - 1 in. (25.4-mm mandrel, no crack or break)
Dimensional Stability:	ASTM F2199 - Passes - no greater than 0.020 in./lin. Ft. (0.51 mm/305 mm)
Static Load:	ASTM F970 - Passes - Exceeds 1000 psi
Residual Indentation:	ASTM F1914 - Passes - average less than 8%
Resistance To Chemicals:	ASTM F925 - Passes - no change
Resistance To Light:	ASTM F1515 - Passes - less than 8 ave., max
Resistance To Heat:	ASTM F1514 - Passes - less than 8 ave., max
Critical Radiant Flux:	ASTM E648 - Passes - > 0.45 watts/cm ² , Class 1

SUSTAINABILITY

Certification:	FloorScore® certified
----------------	-----------------------

SERVICE

Warranties:	Lifetime Residential, Limited 10 Year Commercial
-------------	--



5101
Acacia



5104
Cocoa



5106
Driftwood



5105
Gunstock



5107
Old English



5108
Reclaimed Oak



5103
Timber Ridge



5102
Weathered Oak




6102
Creme



6101
Casa



6103
Slate



6104
Carrara